

# Graffiti Cleaner

Water Soluble – Biodegradable –  
Eco-Friendly Graffiti Removing Power Gel

## FEATURES

**Advantages:**

Removes most graffiti from Altex high performance gloss finishes - E-Line® 379 & Carbothane® 130 Clear Coat.

- User-friendly light gel structure keeps applied Graffiti Cleaner in place – improves cleaning efficiency
- Spray or brush on, high pressure water wash off
- Simple application; does not require sophisticated application equipment
- No strong chemical smell
- Environmentally friendly and biodegradable using a proprietary blend of the latest developments in eco-friendly solvents
- Cleaning action may be seen as it happens
- Requires no dilution or mixing, use as is
- Over 50% of active components are non VOC according to EU legislation (1999/13/EC) and US legislation (CARB/ EPA 40FR 59.203(f))

## RECOMMENDED USES

**Altex Graffiti Cleaner** is a ready to use, low odour, virtually non-flammable, and biodegradable cleaning solution formulated to remove most graffiti materials from both E-Line® 379 and Carbothane® 130 Clear coated masonry, concrete, steel, or other substrates.

Suitable for use to remove spray paint, markers, crayons and most types of other graffiti materials.

**Altex Graffiti Cleaner** is specially formulated not to damage E-Line 379® \*\* even when used repeatedly strictly according to directions.

\*\*For known graffiti 'hot-spots' it is recommended to apply Carbothane® 130 Clear Coat over the decorative colour base-coat to improve long-term and repeated graffiti removal.

**Limitations of Use:** Aged graffiti and some more sophisticated enamel graffiti paints may be very difficult to remove. Multiple applications of **Altex Graffiti Cleaner** may be required; however, some old graffiti may not be removed. Use only with E-Line® 379 or Carbothane® 130 Clear Coat. This cleaner may soften other similar but less densely cross-linked coatings. Graffiti on rough or porous surfaces will be difficult to remove and may require several passes.

## SPECIFICATION DATA

**Coating Type:** Eco-Solvent based graffiti cleaner  
**Colours:** Clear, may yellow slightly over time  
**Packaging:** 4 litre  
**Mix Ratio:** Single package, use undiluted  
**Flash Point:** >100°C  
**Storage:** Store under cool, dry conditions

**Density:** 1.05 kg per litre  
**Volume solids:** 4.14%  
**VOC:** 323 gm / litre (see "Features" above)  
**Application:** Pump-spray or brush  
**Consumption Rate:** Approximately 5 m<sup>2</sup> per litre per pass

## DIRECTIONS FOR USE

### Application Equipment:

- Clean rags
- Soft natural bristle brush
- 1 litre high density polyethylene or polypropylene hand-pump spray bottle
- Neoprene™ or butylrubber gloves
- Safety goggles
- An industrial type pressurised sprayer may be used. However for equipment dedicated to cleaning graffiti Teflon seals and gaskets with ultra-high chemical resistant hoses should be used. Do not use rubber gaskets. Prolonged contact with rubber materials may cause swelling and deterioration

### Graffiti Removal:

1. Before use gently shake **Altex Graffiti Cleaner** to disperse the gel evenly through the mixture.
2. Apply **Altex Graffiti Cleaner** directly to graffiti.
3. Wait approximately 3 to 5 minutes. In hot or windy conditions it may be necessary to keep the area moist with **Altex Graffiti Cleaner**, then wipe with clean rags or HP water wash away. If more than two applications of **Altex Graffiti Cleaner** are needed to remove stubborn stains, rinse the area with clean water and wipe dry before each additional application.
4. Masonry walls or aged graffiti may require scrubbing with a soft natural bristle brush.
5. Avoid **Altex Graffiti Cleaner** contact with rubber materials such as gaskets, etc. Swelling may occur on prolonged contact.
6. Rinse all **Altex Graffiti Cleaner** cleaned surfaces with water.
7. Allow surface to dry.
8. Discard wiping rags in closed container

**Note:** Wear safety goggles and gloves. Avoid prolonged skin contact with **Altex Graffiti Cleaner**.

## PRECAUTIONS

For industrial use only. Read and follow all the caution statements on this Product Data Sheet, the product label and the Safety Data Sheet (SDS) for health and safety information prior to use.

Under extreme conditions **Altex Graffiti Cleaner** may be flammable. Keep away from heat, sparks and open flame. Use with adequate ventilation. May cause eye and skin irritation. Do not breathe vapour or spray. Wear suitable protective clothing such as gloves and eye and face protection.

## WWW.ALTEXCOATINGS.COM

### Head Office New Zealand

#### Altex Coatings Ltd

91-111 Oropi Road  
Greerton, Tauranga 3112

Ph: +64 7 541 1221  
Fax: +64 7 541 1310

### Head Office Australia

#### Resene Paints (Aust) Ltd Industrial & Marine Division

7 Production Avenue, Molendinar  
Queensland 4214

Ph: +61 7 5512 600  
Fax: +61 7 5512 697

### DISCLAIMER

The information in this datasheet is provided as a guide only and is provided without warranty, implied or otherwise. It is your responsibility to determine the suitability of any information or product for the use contemplated. Conditions of use, application and the substrate are beyond our control so no liability whatsoever (whether as to coverage, performance, injury or otherwise) is accepted for the information contained herein.

Data sheets may change from time to time and it is your responsibility to ensure you have the latest product datasheet and material safety data sheet from your supplier. Check the data sheet date with the listings at [www.altexcoatings.com](http://www.altexcoatings.com)  
Altex Terms and Conditions of Trade, available at [www.altexcoatings.com](http://www.altexcoatings.com), apply in respect of all coating products and materials supplied, including samples.